

zBoost Metro - YX540iP iPhone Signal Booster

Extend iPhone Signal Indoors for Condos, Lofts and



Designed for use in single-story urban living, the Wi-Ex zBoost Metro YX540iP cell phone signal booster boosts indoor signal for multiple users operating any mobile device that uses the 800 and 1900 MHz frequencies--including AT&T, T-Mobile, Verizon Wireless, and Sprint (but not Nextel phones). The zBoost Metro YX540iP is optimized for use with Apple iPhone. Take full advantage of your iPhone's voice, data and Internet services, including 3G high-speed data, streaming video, instant messaging, sending pictures, and more.

Easy installation: Package includes everything you need: Base Unit, Base Antenna, low-loss cable (35', RG59-mini), Window-mount Signal Antenna and Power Supply. Includes multiple patent pending technologies to provide low-cost coverage while continually adapting to signals to prevent interference and remain transparent to the wireless network.

Benefits include:

- Perfect for single story settings – no vertical antenna separation needed
- Compatible with all U.S. carriers and mobile devices using 800 & 1900 MHz and optimized for iPhone (except Nextel/iDEN or 4G, 2100MHz phones)
- Increases indoor signal coverage – up to 1500 sq ft
- Supports multiple users simultaneously
- Increases voice and data transmission
- Decreases dropped or missed calls
- Easy to set up – comes with everything you need
- No cradle or connections to your iPhone
- Extends battery life (uses less power when signal is stronger)
- Protects the carrier network using patented technology

Easy to set up – comes complete with everything needed



Product Specifications for zBoost METRO – YX540iP Dual Band

PCS band	
Frequency	Uplink:1850 to 1910 MHz Downlink: 1930 to 1990 MHz
System Gain	54dB
PCS band supported	A, D, B, E, F, C
Networks	CDMA, GSM, GPRS, EDGE, EVDO, 1xRTT, UMTS, HSPA, 3G
Cellular band	
Frequency	Uplink: 824 to 849 MHz Downlink: 869 to 894 MHz
System Gain	52dB
Cellular band supported	A, B, A', B'
Networks	CDMA, GSM, GPRS, EDGE, EVDO, 1xRTT, UMTS, HSPA, 3G
General	
Power Consumption – Power Supply Current	3W standby; 7W max signal - 2.0A Max
Wall Supply Input ; Voltage	100-240VAC 50-60 Hz ; 5.0VDC
System Certifications	FCC Parts 15 & 24 (PCS) and Parts 15 & 22 (CEL), Industry Canada
Base Unit Size and Weight	5" x 7" x 1.25" – 9 oz.
Operating Conditions	Indoor Use Only (40 °- 105° F)
Coverage (open areas)	Over 1500 sq ft in ideal conditions

Product coverage is limited by setup and antenna isolation. Handles all PCS or CEL protocols and includes multiple patent pending technologies to provide low-cost coverage while continually adapting to signals to prevent interference and remain transparent to the wireless network. Provides an indicator if the antennae are positioned improperly, but will NOT suffer damage or interfere with the Carrier Network.